

## Moisture-adaptive Flashing Tape for Indoors and Outdoors

# Hanno®-Flashing Tape DUO Easy BASIC 180



### Full-surface self-adhesive




Hanno®-Flashing Tape DUO Easy BASIC 180 consists of a modified polyamide film/nonwoven combination. The full-surface self-adhesive underside enables simple, full-coverage installation of the flashing tape for plastering or painting over, without additional adhesion on the masonry. DUO Easy+ BASIC 180 has an additional adhesive strip on the opposite side.

Hanno®-Flashing Tape DUO Easy BASIC 180 was designed especially for curtain-type window elements often used for energy efficient constructions. It is moisture-variable and therefore can be used both inside and outside.




The strong water tightness in heavy rain of  $> 1050$  Pa prevents the penetration of moisture on the weather side. On the inside, the important airtightness is achieved with an  $a_n$ -value of  $< 0.1$ .

### Properties

- For indoor and outdoor use
- Variable moisture adaptation
- Strong water tightness in heavy rain and air tightness
- Full-surface adhesive; no additional foil adhesive required
- UV stable for 3 months
- Water tightness in heavy rain EN 1027  $\geq 1050$  Pa, MPA
- Resistance to water permeation acc. to EN 1928



Fitting Hanno®-Flashing Tape DUO Easy BASIC 180



Fitting Hanno®-Flashing Tape DUO Easy+ BASIC 180

Hanno Werk GmbH & Co. KG

Hanno-Ring 3-5  
30880 Laatzen  
Germany

Phone: +49 5102 7000-0  
info@hanno.com  
www.hanno.com



QM system certified  
according to IATF 16949: 2016  
and ISO 9001: 2015